



"समृद्ध समावेशी र सुखी बेनीघाट लेसङ्ग आधारः कृषि शिक्षा स्वास्थ्य उद्योग सुशासन र पर्यावरण"

बेनीघाट रोराड गाउँपालिका

गाउँ कार्यपालिकाको कार्यालय



प.सं. २०८२/०८३

च.नं. २९९९

विशालटार, धादिङ्ग
बागमती प्रदेश, नेपाल



मिति: २०८३।०२।०५

श्री जो जससँग सम्बन्धित छ ।

विषय: दररेट पेश गर्ने सम्बन्धमा ।

प्रस्तुत विषयमा यस गाउँपालिकाको लागि आवश्यक यसै साथ संलग्न स्पेशिफिकेशन बमोजिम तपसिलमा उल्लेखित विवरणका एयर कन्डिसन (ए.सी.) खरिद गर्ने निर्णय भएको र उक्त एयर कन्डिसन (ए.सी.) खरिदको लागि लागत अनुमान तयार गर्ने प्रयोजनार्थ प्रचलित बजार मूल्य आवश्यक रहेकोले संलग्न स्पेशिफिकेशन बमोजिमको एयर कन्डिसन (ए.सी.) प्रचलित बजार मूल्यको आधारमा प्रति एकाई दररेट दररेट उल्लेख गरी पत्रको मितिले ३ (तीन) दिन भित्र यस कार्यालयमा उपलब्ध गराईदिनुहुन अनुरोध गरिन्छ ।

तपसिल

क्र.सं.	विवरण	क्षमता	प्रति एकाई दर	कैफियत
१	एयर कन्डिसन (संलग्न स्पेशिफिकेशन बमोजिम)	१ टन		
२	एयर कन्डिसन (संलग्न स्पेशिफिकेशन बमोजिम)	१.५ टन		
३	एयर कन्डिसन (संलग्न स्पेशिफिकेशन बमोजिम)	२ टन		

शर्तहरू:

१. दररेट मूल्य अभिवृद्धि कर (VAT) बाहेक वा सहित के हो ? प्रष्ट खुलाउनुपर्नेछ ।
२. सामानको गुणस्तर कार्यालयले तोकेको विशिष्टता (Specification) बमोजिम हुनुपर्नेछ ।
३. दररेट पेश गर्दा फर्म दर्ता प्रमाणपत्र, भ्याट/प्यान दर्ता र आ.व. २०८१/०८२ को कर चुक्ता प्रमाणपत्रको प्रतिलिपि समेत संलग्न राख्नुपर्नेछ ।

.....

रामबाबु पौडेल

प्रमुख प्रशासकीय अधिकृत

Er. Nishan Timilsina

NEC License No.: 5524
Mobile: +977-9845178567
VAT No: 126351284

Address

Chyasal, Lalitpur
Email: nishantimilsina329@gmail.com

TECHNICAL SPECIFICATIONS

Date: 2083/01/15
Ref: TS-09-082/083

To,
Benighat Rorang Rural Municipality
Benighat, Dhading.

S.N.	Items Name	Category	Parameter	Detailed Technical Requirements	Bidder's Offers	Remarks
1	Air Condition 2.0 Ton	GENERAL	Descriptions	Supply, delivery, installation, testing and commissioning of Split Type Air Conditioners (Wall Mounted) complete with all accessories, piping, wiring, and necessary civil works.		
			Brand & Model	To be purposed by bidders		
			Capacity	2.0Ton,24000 BTU/h (Nominal)		
			AC Type	Split Wall Mounted - DC Inverter Technology		
			Star Rating	5 Star (High Efficiency / ISEER 4.5+)		
		PERFORMANCE	Cooling Capacity (Min-Max)	6900W-7100W		
			Heating Capacity (Optional)	6900W-7100W		
			Air Flow Volume (IDU)	650 m ³ /h (High) / 520 m ³ /h (Med) / 410 m ³ /h (Low)		
			Sound Level (IDU)	Silent Mode: 24dB / High: 38dB		
			Sound Level (ODU)	≤ 52 dB(A)		
			Operating Range	15°C to 52°C Ambient Temperature		
			Moisture Removal	1.5-2.5 Liters/Hour		
		ELECTRICAL	Power Supply	Single Phase, 220-240V, 50Hz		
			Rated Power Input	1900-2500 Watts (at standard conditions)		
			Rated Current	10Amps		
			Maximum Current	15 Amps		
			In-built Stabilizer	Supported Range: 135V - 290V		
		REFRIGERATION	Refrigerant Type	R32 (Eco-Friendly, Zero ODP, Low GWP)		
			Condenser Coil	100% Grooved Copper for better heat exchange		
			Evaporator	Golden Fin Anti-Corrosive Coating (Salt Spray Resistant)		
			Expansion Valve	Electronic Expansion Valve (EEV) for precision		
		FEATURES	Air Filtration	Anti-Bacterial + PM 2.5 + Vitamin C Filter		
			Swing Type	4-Way Auto Swing (Horizontal & Vertical)		
			Smart Connectivity	In-built Wi-Fi, App Control (Matter Compatible)		
			Display	Magic LED Display (Hidden Type)		
Modes	Turbo, Sleep, Eco, Dry, Fan					

Er. Nishan Timilsina
NEC Regd. No.: 5524
Mechanical "A"

Nishan Timilsina

			Only, i-Feel		
		Self-Cleaning	i-Clean Technology (Frost Wash at -15°C)		
	PHYSICAL	IDU Dimensions (WxHxD)	Approx. 850 x 290 x 210 mm		
		ODU Dimensions (WxHxD)	Approx. 780 x 540 x 260 mm		
		Net Weight (IDU/ODU)	12.0-15.0 kg / 35.0-45.0 kg		
		Connecting Pipe Length	3.5 Meters (Standard Kit Included)		
		Max Pipe Length / Height	15 Meters / 7 Meters		
	WARRANTY	Compressor	10 Years Limited Warranty		
		PCB/Parts	1 Year Comprehensive + 2 Years on PCB		

Note: The major items are indicated by Bold and highlighted letters/alphabets/figures in the technical specifications. Non-compliance of these major items will result in no responsiveness of the bid.

Prepared By:

Nishan Timilsina

.....
Er. Nishan Timilsina

Er. Nishan Timilsina
NEC Regd. No.: 5524
Mechanical "A"

Er. Nishan Timilsina

NEC License No.: 5524
Mobile: +977-9845178567
VAT No: 126351284

Address

Chyasal, Lalitpur
Email: nishantimilsina329@gmail.com

TECHNICAL SPECIFICATIONS

Date: 2083/01/15
Ref: TS-10-082/083

To,
Benighat Rorang Rural Municipality
Benighat, Dhading.

N.	Items Name	Category	Parameter	Detailed Technical Requirements	Bidder's Offers	Remarks
1	Air Condition 1.0 Ton	GENERAL	Descriptions	Supply, delivery, installation, testing and commissioning of Split Type Air Conditioners (Wall Mounted) complete with all accessories, piping, wiring, and necessary civil works.		
			Brand & Model	To be purposed by bidders		
			Capacity	1.0 Ton / 12,000 BTU/h (Nominal)		
			AC Type	Split Wall Mounted - DC Inverter Technology		
			Star Rating	5 Star (High Efficiency / ISEER 4.5+)		
		PERFORMANCE	Cooling Capacity (Min-Max)	3400W/3600W		
			Heating Capacity (Optional)	3400W/3600W		
			Air Flow Volume (IDU)	650 m ³ /h (High) / 520 m ³ /h (Med) / 410 m ³ /h (Low)		
			Sound Level (IDU)	Silent Mode: 24dB / High: 38dB		
			Sound Level (ODU)	≤ 52 dB(A)		
			Operating Range	15°C to 52°C Ambient Temperature		
		ELECTRICAL	Moisture Removal	1-2 Liters/Hour		
			Power Supply	Single Phase, 220-240V, 50Hz		
			Rated Power Input	900-1500Watts (at standard conditions)		
			Rated Current	4.0 Amps		
			Maximum Current	7 Amps		
		REFRIGERATION	In-built Stabilizer	Supported Range: 135V - 290V		
			Refrigerant Type	R32 (Eco-Friendly, Zero ODP, Low GWP)		
			Condenser Coil	100% Grooved Copper for better heat exchange		
			Evaporator	Golden Fin Anti-Corrosive Coating (Salt Spray Resistant)		
		FEATURES	Expansion Valve	Electronic Expansion Valve (EEV) for precision		
			Air Filtration	Anti-Bacterial + PM 2.5 + Vitamin C Filter		
			Swing Type	4-Way Auto Swing (Horizontal & Vertical)		
			Smart Connectivity	In-built Wi-Fi, App Control (Matter Compatible)		
			Display	Magic LED Display (Hidden Type)		
		Modes	Turbo, Sleep, Eco, Dry, Fan Only, i-			

Er. Nishan Timilsina
NEC Regd. No.: 5524
Mechanical "A"

Nishan Timilsina

			Feel		
		Self-Cleaning	Self-Cleaning		
	PHYSICAL	IDU Dimensions (WxHxD)	Approx. 850 x 290 x 210 mm		
		ODU Dimensions (WxHxD)	Approx. 780 x 540 x 260 mm		
		Net Weight (IDU/ODU)	8-10 kg / 20-26.0 kg		
		Connecting Pipe Length	3.5 Meters (Standard Kit Included)		
		Max Pipe Length / Height	15 Meters / 7 Meters		
	WARRANTY	Compressor	10 Years Limited Warranty		
		PCB/Parts	2 Year Comprehensive + 2 Years on PCB		

Note: The major items are indicated by Bold and highlighted letters/alphabets/figures in the technical specifications. Non-compliance of these major items will result in no responsiveness of the bid.

Prepared By:

Nishan Timilsina

.....
Er. Nishan Timilsina

Er. Nishan Timilsina
NEC Regd. No: 5524
Mechanical "A"

Er. Nishan Timilsina

NEC License No.: 5524
Mobile: +977-9845178567
VAT No: 126351284

Address

Chyasal, Lalitpur
Email: nishantimilsina329@gmail.com

TECHNICAL SPECIFICATIONS

Date: 2083/01/15
Ref: TS-08-082/083

To,
Benighat Rorang Rural Municipality
Benighat, Dhading.

S.N	Items Name	Category	Parameter	Detailed Technical Requirements	Bidder's Offers	Remarks
1	Air Condition 1.5 Ton	GENERAL	Descriptions	Supply, delivery, installation, testing and commissioning of Split Type Air Conditioners (Wall Mounted) complete with all accessories, piping, wiring, and necessary civil works.		
			Brand & Model	To be purposed by bidders		
			Capacity	1.5 Ton / 18000 BTU/h (Nominal)		
			AC Type	Split Wall Mounted - DC Inverter Technology		
			Star Rating	5 Star (High Efficiency / ISEER 4.5+)		
		PERFORMANCE	Cooling Capacity (Min-Max)	5100W-5300W		
			Heating Capacity (Optional)	5100W-5300W		
			Air Flow Volume (IDU)	650 m ³ /h (High) / 520 m ³ /h (Med) / 410 m ³ /h (Low)		
			Sound Level (IDU)	Silent Mode: 24dB / High: 38dB		
			Sound Level (ODU)	≤ 52 dB(A)		
			Operating Range	15°C to 52°C Ambient Temperature		
			Moisture Removal	1-2 Liters/Hour		
		ELECTRICAL	Power Supply	Single Phase, 220-240V, 50Hz		
			Rated Power Input	1500-1900 Watts (at standard conditions)		
			Rated Current	7.0 Amps		
			Maximum Current	12 Amps		
			In-built Stabilizer	Supported Range: 135V - 290V		
		REFRIGERATION	Refrigerant Type	R32 (Eco-Friendly, Zero ODP, Low GWP)		
			Condenser Coil	100% Grooved Copper for better heat exchange		
			Evaporator	Golden Fin Anti-Corrosive Coating (Salt Spray Resistant)		

Er. Nishan Timilsina
NEC Regd. No: 5524
Mechanical "A"

Nishan Timilsina

		Expansion Valve	Electronic Expansion Valve (EEV) for precision		
	FEATURES	Air Filtration	Anti-Bacterial + PM 2.5 + Vitamin C Filter		
		Swing Type	4-Way Auto Swing (Horizontal & Vertical)		
		Smart Connectivity	In-built Wi-Fi, App Control (Matter Compatible)		
		Display	Magic LED Display (Hidden Type)		
		Modes	Turbo, Sleep, Eco, Dry, Fan Only, i-Feel		
		Self-Cleaning	i-Clean Technology (Frost Wash at -15°C)		
		PHYSICAL	IDU Dimensions (WxHxD)	Approx. 850 x 290 x 210 mm	
	ODU Dimensions (WxHxD)		Approx. 780 x 540 x 260 mm		
	Net Weight (IDU/ODU)		10.5-12.5 kg / 26.0-28.0 kg		
	Connecting Pipe Length		3.5 Meters (Standard Kit Included)		
	Max Pipe Length / Height		15 Meters / 7 Meters		
	WARRANTY	Compressor	10 Years Limited Warranty		
		PCB/Parts	2 Year Comprehensive + 2Years on PCB		

Note: The major items are indicated by Bold and highlighted letters/alphabets/figures in the technical specifications. Non-compliance of these major items will result in no responsiveness of the bid.

Prepared By:

Nishan Timilsina

.....
Er. Nishan Timilsina

Er. Nishan Timilsina
NEC Regd. No.: 5524
Mechanical "A"